



KHT 5005.2

home theatre



Specifications	HTS/HTC5001	Specifications	HTB2
Design	Satellite speaker / Centre Speaker - three way closed box	Design	Powered Subwoofer Passive radiator
Drive Units	75mm (3in.) UNI-Q® array with 15 mm (0.6 in.) HF, 2x75mm (in.)LF	Drive Units	1 x 250mm (10in.) 1 x 250mm (10in.) ABR
Frequency range	95Hz - 30kHz	Frequency range	30Hz - 250Hz
Power Handling	100 W	Power Handling	100-240v ac 50-60Hz
Sensitivity (2.83V/1m)	87dB	Amplifier	250 Watts built in
Maximum output (SPL)	106dB	Maximum output (SPL)	110dB SPL @ 1m
Impedance	8 ohms	Internal volume	15 litres
Internal volume	1.4 litres	Weight	11.3kg (24.9lbs)
Weight	2 kg (4.4 lbs)	Dimensions (H x W x D)	vertical: 390 x 440 x 195 mm 15.4 x 17.3 x 7.7 in. horizontal: 227 x 440 x 385 mm 8.9 x 17.3 x 7.7 in.
Dimensions (H xW xD)	419 x 88x 127mm 16.5 x 3.46 x 5.0 in	Cabinet finishes	High Gloss Black or High Gloss Silver
Cabinet finishes	Matt Silver or High Gloss Black		