

S Y N E R G Y

Synergy Sub-10 Specifications



FREQUENCY RESPONSE	28Hz-120Hz +/- 3dB
POWER HANDLING	FTC Rated Power: 200 watts continuous @ 1% THD, Dynamic Power*: 420 watts *Dynamic power indicates the actual power this amplifier will deliver to the woofer under normal operating conditions. While the FTC power rating indicates power available on a continuous, long-term basis, subwoofers do not rely on that type of power. Instead, the amplifier is called upon to deliver large, short-term peaks of power to be able to support the wide dynamics required by today's digital music and movie formats. In addition to the required FTC power rating, we've provided the dynamic power rating as a better indication of the product's true performance
CROSSOVER FREQUENCY	Continuously variable from 40Hz-120Hz, 24dB/octave slope above 120Hz
MAX CONTINUOUS OUTPUT	115dB @30 Hz 1/8 space 1 meter
WOOFER	One 10" (25.4cm) driver
AMPLIFIER	BASH
PHASE	Switchable 0-180 degrees
ENCLOSURE TYPE	Bass-reflex via rear-firing, 4.125-inch round port
INPUT CONNECTIONS	Two line level/RCA phono jacks and two high level speaker terminals
AUTO POWER ON	2 second ON delay; 15 minute OFF delay
DIMENSIONS	17" (43.2cm) H x 14.0" (35.6cm) W x 18.875" (47.9cm) D
WEIGHT	37 lbs. (16.8kg)
FINISHES	Black
VOLTAGE	110/120 VAC 60Hz
EXPORT VOLTAGE	230v
BUILT FROM	2005

THE ULTIMATE SOUND EXPERIENCE™

