

## RSB-6



### TRUE 2-WAY BI-AMPLIFIED SOUND BAR

Two 3/4" horn-loaded textile dome tweeters with 90° x 90° Tractrix® horns deliver crisp highs, while two 2 3/4" woofers round out the enhanced sound with clear vocals and dynamic soundtracks. Includes DSP-controlled crossover via separate amplifier channels for tweeter and woofer.

### HDMI 2.0 FOR 4K VIDEO PASS THROUGH

Whether or not you already have a 4K TV, the Klipsch Reference RSB-6 sound bar is the best choice for superior sound from your current TV. One HDMI 2.0 input with HDCP 2.2 compatibility allows for easy connection of your cable/DSS box, Blu-Ray player, and gaming system. One HDMI cable out to your TV provides for a superior picture. One HDMI cable is included.

### OPTICAL AND ANALOG AUDIO INPUTS

If you haven't made the jump to a TV with HDMI yet, we've included an Optical Digital (TOSLink) and Analog input.

### BUILT-IN DOLBY AUDIO® DECODING

Dolby Audio decoding provides crystal clear audio and prevents jumps in volume as you switch content or go from broadcast programs to commercial breaks.

### 6.5-INCH WIRELESS SUBWOOFER

With a 6.5-inch downward-firing driver and professionally-tuned slot port cabinet, the RSB-6 delivers earth-shaking bass worthy of a movie theater.

### COMPATIBLE WITH MOST BLUETOOTH® WIRELESS ENABLED DEVICES

Including mobile phones, audio devices, and computers for wide-ranging use.

### VIRTUAL SURROUND MODE

Klipsch optimized surround sound.

### DIALOGUE ENHANCE MODE

Increases the dialogue volume for enhanced vocal clarity without increasing ambient sounds.

### NIGHT MODE

Adjusts dynamic range for quieter listening environments.

### WIRELESS REMOTE CONTROL

An easy-to-use wireless remote control is included in the box.

### FLEXIBLE PLACEMENT OPTIONS

Keyhole mounts for easy wall mounting and rubber feet for stable, on-TV stand placement are included.

## SPECIFICATIONS

SPEAKER SYSTEM	2-way sound bar with 6.5" wireless subwoofer
MAX ACOUSTIC OUTPUT	103dB @ 1 meter
HIGH FREQUENCY DRIVERS	2 x 3/4" (19mm) soft dome tweeters mated to dual 90° x 90° Tractrix horns
MIDRANGE	2 x 2.5" (63.5mm) fiber composite cone woofers
SUBWOOFER	6.5" (165.1mm) downward-firing fiber composite cone
ENCLOSURE TYPE (BAR)	Ported
ENCLOSURE TYPE (SUB)	Ported
SYSTEM POWER	Total System Power: 60 watts continuous @ <0.5% THD 120 watts short-term peak power
FREQUENCY RESPONSE	30Hz ~ 15kHz @ +/- 3dB
INPUTS	1 x HDMI 2.0 with HDCP 2.2 compatibility Optical Digital 3.5mm miniplug (analog) Bluetooth® 2.0
TYPICAL MAXIMUM OUTPUT	106dB SPL (in-room)
OUTPUTS	1 x HDMI 2.0 with HDCP 2.2 compatibility
DIMENSIONS	Sound Bar: 40" (101.6cm) x 3.75" (9.53cm) x 3.75" (9.53cm) Subwoofer: 7.375" (18.74cm) x 10.5" (26.67cm) x 13.5" (34.29cm)
FINISH	Black
VOLTAGE	110/120 VAC
WEIGHT	Sound Bar: 6.5lbs (2.95kg) Subwoofer: 9.6lbs (4.35kg)
BUILT FROM	2016
INCLUDED ACCESSORIES	One 1.5m HDMI cable, one pair of rubber feet, one wall mounting template, one wireless remote control, two power supplies (one for sound bar and one for subwoofer)



**Klipsch®**  
KEEPERS OF THE SOUND

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM

All specifications are subject to change without notice. ©2016 Klipsch Group, Inc. Klipsch, Keepers of the Sound and Tractrix are registered trademarks of Klipsch Group, Inc. a wholly-owned subsidiary of Vox International Corporation. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Klipsch Group, Inc. is under license. aptX® software is copyright CSR plc or its group companies. All rights reserved. The aptX® mark and the aptX logo are trademarks of CSR plc or one of its group companies and may be registered in one or more jurisdictions. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.